



TECHNICAL DATA OF RV-HW2-1050(102323)

Feature:

- 1.Safe and Durable.
- 2.High tensile, tear and adhesion strength.
- 3.Excellent ability on Waterproof, anti-UV, fire retardant, mouldproofing, antiabrasion and self-cleaning for option
- 4.Good resilience, Outstanding opacity.
- 5.Ideal for inflatable boat, swimming pool liner, tent, truck cover, side curtain,high-ends projects, mega marquees, or mobile constructions at harsh conditions.

Specification:

Base fabric	1000Dx1000D 23x23/sq.yd 1100dtex x1100dtex 9x9/sq.cm	DIN 53830/DIN60001 ASTM D 751
Weight	1050gsm+/- 20gsm	DIN53352
Lacquering	31oz	ASTM D 751
Breaking strength (Warp/weft)	2980/2095 N/5cm 669lbs/553lbs/2"	DIN 53354 FS 5100
Tearing strength	469/390 N/5cm 105lbs/91lbs	DIN 53363 FS 5100
Adhesion strength	110N/5cm 25lbs/2"	DIN 53357 FS 5970
Avilable width	1000-3200mm 36"-126"	
Fire retardant	M2, B1, NFPA 701, B2	
Temperature resistance	- 30°C ~ 70°C - 20°F ~ 158°F	DIN 53372 FS 5874

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

